

AC/DC Battery Integrated Charger 240kW/280kW, Floor-Mounted

 Datasheet


2025



 Reliable

Product
Reliability

99%

 Cloud Enabled

Monitoring
& Assistance









24/7










 Built To Last

Service
Life

10Y

Key Features

-  215kWh integrated battery, with 22kW AC input
-  Dual tethered connectors allow for simultaneous charging of two vehicles
-  Remote software updates and diagnostics
-  Seamless integration with OCPP 1.6j protocol
-  Supports multiple payment options — app, RFID, credit card, and smartphone payments
-  Supports multiple output options: CCS1, CCS2 and CHAdeMO
-  3-year warranty with an optional 2-year extension
-  Approved for OZEV grant eligibility

<div> AC INPUT</div>	AC Input	380/400VAC (±15%) 50/60Hz
	Power Supply System	3P+N+PE (Wye Configuration), TN/TT
	FLA II Breaker Rating	100A / 125A
	Rated Input Power	60kW
	Power Factor	> 0.98 @ full load
	Efficiency	> 94% at normal output power
<div> ENERGY STORAGE</div>	Energy Chemistry	Lithium-Ion
	Energy Storage Capacity	208kWh
<div> DC OUTPUT</div>	Rated Output Power	240kW/280kW
	Max Output Voltage	150 ~ 1000VDC
	Max Output Current	CCS2: 350A GBT: 250A CHAdEMO: 200A
	Connectors	CCS2, GBT and CHAdEMO
	Operating Temperature	-4°F to 122°F (-20°C to 50°C)
<div> ENVIRONMENT</div>	Altitude	≤ 6561ft (2000m)
	Operating Humidity	5% to 95%RH, non-condensing
	Protective Class	IP54, IK10 (not including screen)
	Cooling System	Air Cooling Fans
<div> COMMUNICATION</div>	Communication	Ethernet, Wi-Fi, 4G
	Interface Protocol	OCPP 1.6J
<div> USER INTERFACE</div>	Display	32"LCD Touch Screen
	Access Control	RFID : ISO/IEC 14443A/B Credit Card Reader - Optional
	Emergency Stop	Operation buttons/Disables Output Power
	Dimension Wall Mount (W X D X H) / Weight	TBD / TBD
<div> MECHANICAL</div>	Connector Cable Length	CCS2 - 16 ft (5 m) CHAdEMO - 16 ft (5 m) GBT - 16 ft (5 m)
	Cable Management	Included
	Input Protection	RCD, Surge Protection Over Voltage, Under Voltage, Over Current
<div> PROTECTION</div>	Output Protection	Short circuit protection Insulation protection Over temperature protection
	Charging Protocol	ISO-15118 , DIN 70121, GB/T 27930 , CHAdEMO 0.9, 1.0
	Standard	IEC 61851-1, IEC 61851-23, IEC 61851-21-2
<div> REGULATION</div>	Certificate	CE