

AdVision DC Charger 60kW, Floor-Mounted

 Datasheet

2025



Reliable

Product
Reliability

99%

Cloud Enabled

Monitoring &
Assistance

24/7









Built To Last

Service
Life

10Y

Key Features

- Dual tethered connectors allow for simultaneous charging of two vehicles
- Remote software updates and diagnostics
- Seamless integration with OCPP 1.6J / 2.0 / 2.0.1 protocol
- Supports multiple payment options — app, RFID, credit card, and smartphone payments
- Three-phase connection
- 10"LCD Touch Screen and 32"LCD Colour Screen
- 3-year warranty with an optional 2-year extension
- Supports multiple output options: CCS2, GBT and CHAdeMO

 AC INPUT	AC Input	380/400VAC (±15%) 50Hz
	FLA Breaker Rating	100A / 125A
	Efficiency	≥ 94% at nominal output power
 DC OUTPUT	Output Voltage Range	150-1000VDC
	Max Output Current	CCS2 : 150A GBT : 150A CHAdeMO : 150A
	Connectors	CCS2 and GBT and CHAdeMO
	Connectors Quantity	2
	Operating Temperature	-4°F to 122°F (-20°C to 50°C)
 ENVIRONMENT	Protective Class	IP54
	Communication	Ethernet, Wi-Fi, 4G
 COMMUNICATION	Interface Protocol	OCPP 1.6J/2.0/2.0.1
	Display	10" LCD Touch Screen and 32" LCD Colour Screen
 USER INTERFACE	Access Control	RFID : ISO/IEC 14443A/B Credit Card Reader - Optional
	Dimension Wall Mount (W X D X H)	39.96" x 29.73" x 81.11" (1015mm x 755mm x 2060mm)
 MECHANICAL	Weight	727lbs (330kg)
	Connector Cable Length	CCS2 - 16 ft (5 m) CHAdeMO - 16 ft (5 m) GBT - 16 ft (5 m)
	Input Protection	Surge Protection Over Voltage, Under Voltage (Optional) Over Current, Missing Ground (Optional)
 PROTECTION	Output Protection	Short circuit protection Insulation protection Over temperature protection
	Charging Protocol	ISO-15118 , DIN 70121, GB/T 27930 , CHAdeMO 0.9, 1.0
 REGULATION	Regulatory Compliance	IEC 61851-1, IEC 61851-23, IEC 61851-21-2
	Certificate	CE