

AdVision V2G DC Charger 80kW, Floor-Mounted

 Datasheet

2025



Intertek



Reliable

Product
Reliability

99%

Cloud Enabled

Monitoring
& Assistance

24/7

Built To Last

Service
Life

10Y

Key Features

- Single or dual tethered connector
- Remote software updates and diagnostics
- Seamless integration with OCPP 1.6J / 2.0 / 2.0.1 protocol
- Supports multiple payment options — app, RFID, credit card, and smartphone payments
- Three-phase connection
- Rapid charging
- Connector option: CCS2
- 7" LCD Touch Screen and 32" LCD Colour Screen
- 3-year warranty with an optional 2-year extension
- Approved for OZEV grant eligibility

| | | |
|--|--------------------------|--|
|  CHARGING MODE | AC Input | 380/400 II 50Hz / 60Hz |
| | Rated Output Power | 80kW Three-phase |
| | FLA II Breaker Rating | 135A / 250A |
| | Connector Options | CCS2 |
| | Maximum Power | 80kW |
| | Output Voltage | 150-1000VDC |
| | Output Current | 0 ~ 200A |
| | Connector Quantity | 1 / 2 |
| | Efficiency | ≥ 94% at nominal output power |
| | Charging Protocol | ISO 15118, DIN 70121 |
|  DISCHARGING MODE | Length of Charging Cable | 16ft (5m) |
| | DC Input (V) | 300-1000VDC |
| | AC Output (A) | 180A Max |
| | AC Output (V) | 300/480VAC |
| | Efficiency | ≥ 94% at nominal output power |
|  ENVIRONMENT | Discharging Protocol | ISO 15118 - 20 |
| | Operating Temperature | -4°F to 131°F (-20°C to 55°C) |
|  OTHER | Protective Class | IP54 |
| | Access Control | ISO/IEC 14443A/B |
| | Dimension (W X D X H) | 39.96" x 25.14" x 81.11" (1015mm x 638mm x 2060mm) |
| | Weight | 860lbs (380kg) |
| | Display | 7" Touch Screen and 32" LCD Colour Screen |
| | Communication | Ethernet, Wi-Fi, 4G |
| | Interface Protocol | OCPP 1.6J/2.0/2.0.1 |
|  ELECTRICAL SAFETY | AC Port Protection | OVP (optional), UVP (optional), OCP, OPP, SPD, OFP, UFP, Anti-Islanding Protection |
| | DC Port Protection | OCP, OVP, UVP, OTP, SCP, IMD |
|  REGULATIONS | Compliance | IEC 61851-1, IEC 61851-23, IEC 61851-21-2 EN 50549-1:2019/AC:2019, EN 50549-10:2022 |
| | Certificate | CE |