

AdVision V2G DC Charger Dual 40kW, Floor-Mounted

Datasheet

2025



Intertek



✓ Reliable

Product
Reliability

99%

✓ Cloud Enabled

Monitoring
& Assistance

24/7







✓ Built To Last

Service
Life

10Y

Key Features

- ✓ Dual connectors allow for simultaneous charging of two vehicles
- ✓ Remote software updates and diagnostics
- ✓ Seamless integration with OCPP 1.6J / 2.0 / 2.0.1 protocol
- ✓ Supports multiple payment options — app, RFID, credit card, and smartphone payments
- ✓ Three-phase connection
- ✓ Rapid charging
- ✓ Connector option: CCS2
- ✓ 10"LCD Touch Screen and 32"LCD Colour Screen
- ✓ 3-year warranty with an optional 2-year extension
- ✓ Approved for OZEV grant eligibility

 CHARGING MODE	AC Input	380/400 II 50Hz / 60Hz
	Rated Output Power	44kW Three-phase
	FLA II Breaker Rating	65A / 100A
	Connector Options	CCS2
	Maximum Power	44kW
	Output Voltage	150-1000VDC
	Output Current	0 ~ 146.6A
	Connector Quantity	1 / 2
	Efficiency	≥ 94% at nominal output power
	Charging Protocol	ISO 15118, DIN 70121
 DISCHARGING MODE	Length of Charging Cable	16ft (5m)
	DC Input (V)	300-1000VDC
	AC Output (A)	90A Max
	AC Output (V)	300/480VAC
	Efficiency	≥ 94% at nominal output power
 ENVIRONMENT	Discharging Protocol	ISO 15118 - 20
	Operating Temperature	-4°F to 131°F (-20°C to 55°C)
 OTHER	Protective Class	IP54
	Access Control	ISO/IEC 14443A/B
	Dimension (W X D X H)	39.96" x 25.14" x 81.11" (1015mm x 638mm x 2060mm)
	Weight	650lbs (295kg)
	Display	7" Touch Screen and 32" LCD Colour Screen
	Communication	Ethernet, Wi-Fi, 4G
	Interface Protocol	OCPP 1.6J/2.0/2.0.1
 ELECTRICAL SAFETY	AC Port Protection	OVP (optional), UVP (optional), OCP, OPP, SPD, OFP, UFP, Anti-Islanding Protection
	DC Port Protection	OCP, OVP, UVP, OTP, SCP, IMD
 REGULATIONS	Compliance	IEC 61851-1, IEC 61851-23, IEC 61851-21-2 EN 50549-1:2019/AC:2019, EN 50549-10:2022
	Certificate	CE