

DC RAPID CHARGER – S3

300KW — 360KW

 AIR-COOLED, FLOOR MOUNTED

 PRODUCT DATASHEET / MAY 2026



 Reliable

Product Reliability

99%

 Cloud Enabled

Monitoring & Assistance

24/7

 Built To Last

Service Life

10Yr

KEY FEATURES

- ↳ Dual tethered connectors for simultaneous charging of 2 vehicles
- ↳ Remote software updates and diagnostics
- ↳ Seamless integration with OCPP 1.6J / 2.0 / 2.0.1 protocol
- ↳ Multiple payment options — app, RFID, credit card, and smartphone
- ↳ Three-phase connection
- ↳ 10" LCD Touch Screen
- ↳ 2-year warranty



S.A.F.E.



CB



DC RAPID CHARGER – S3

⌂ 300kW

⌂ 360kW

PRODUCT CODE

TP-EVPD200KW

TP-EVPD240KW

⌄ ELECTRICAL INPUT

Supply System	3P+N+PE, TN/TT	
Supply Voltage	400 V AC (±15%)	
Supply Frequency	50 ±1 Hz	
Rated Input Current	500 A	600 A
Power Factor	≥0.98 at 50 – 100% output power	
THD	<5% at 50 – 100% full load	
Charging Efficiency	≥94% at nominal output power	

⌄ ELECTRICAL OUTPUT

Output Voltage Range	150–1000 V DC	
Maximum Current	CCS2: 350 A / GBT: 350 A / CHAdeMO: 200 A	
Maximum Power	300kW	360kW
Maximum Power Per Connector	300kW	360kW
Connector Type	CCS2; GBT; CHAdeMO	
Number of Connectors / Outputs	2	
Cable Length	5 m, others optional	

⌄ CONNECTIVITY AND COMMUNICATION

Network Connectivity	Ethernet (RJ45), Wi-Fi, 4G
Backend Protocol	OCPP 1.6J / 2.0 / 2.0.1

⌄ USER INTERFACE AND ACCESS CONTROL

Display / HMI	10" LCD Touch Screen
LED Status Indication	LED status indication
RFID	RFID: ISO/IEC 14443 A/B; MIFARE, 13.56 MHz
Authentication And Payment	App, QR Code, MAC Authentication (optional), Card Payment (optional)
Metering	2 x DC energy meter, CE-marked

⌄ ENVIRONMENTAL CONDITIONS

Operating Temperature	–25°C to 55°C
Storage Temperature	–30°C to 70°C
Altitude	≤2000 m
Humidity	5% to 95% non-condensing
Ingress And Impact Protection	IP54, IK10 (screen excluded)
Noise	<70 dB

⌄ SAFETY AND PROTECTION

Integrated Protections	MCCB 3P, 630 A	MCCB 3P, 750 A
	Emergency stop button / RDC-DD, 6 mA DC leakage detection / Overvoltage and undervoltage protection / Overcurrent protection / Output PE continuous continuity checking / Surge protection device (SPD), Type 2, fused / 2 x Insulation monitoring / Temperature monitoring	
Physical Security And Access	Key-lock access door	
Special Environmental Protection	Galvanised steel, powder-coated, salt-spray resistant	

DC RAPID CHARGER – S3

⌵ 300kW

⌵ 360kW

PRODUCT CODE

TP-EVPD200KW

TP-EVPD240KW

⌵ MECHANICAL DATA

Dimensions	1305 x 966 x 2286 mm	
Weight	683 kg	723 kg
Mounting	Floor mounted	
Cable Management	Cable support	
Cooling System	Forced-air cooling	

⌵ COMPLIANCE AND STANDARDS

Charging Protocol Support	ISO 15118; DIN 70121; GB/T 27930; CHAdeMO 0.9 / 1.0	
Regulatory Compliance	IEC 61851-1; IEC 61851-23; IEC 61851-21-2	
Certification	CE Marked (LVD, EMC, RoHS)	

End of Table