

DC RAPID CHARGER – S3

60KW

 AIR-COOLED, FLOOR MOUNTED

 PRODUCT DATASHEET / MAY 2026



 **Reliable**

Product
Reliability

99%

 **Cloud Enabled**

Monitoring
& Assistance

24/7

 **Built To Last**

Service
Life

10Yr

KEY FEATURES

- ↳ Dual tethered connectors for simultaneous charging of 2 vehicles
- ↳ Remote software updates and diagnostics
- ↳ Seamless integration with OCPP 1.6J / 2.0 / 2.0.1 protocol
- ↳ Multiple payment options — app, RFID, credit card, and smartphone
- ↳ Three-phase connection
- ↳ 10" LCD Touch Screen
- ↳ 3-year warranty with an optional 2-year extension
- ↳ Supports multiple output options: CCS2, GBT and CHAdeMO



DC RAPID CHARGER – S3

⌂ 60kW

PRODUCT CODE

TP-EVPD060KW

⌄ ELECTRICAL INPUT

Supply System	3P+N+PE, TN/TT
Supply Voltage	400 V AC (±15%)
Supply Frequency	50 ±1 Hz
Rated Input Current	100 A
Power Factor	≥0.98 at 50 – 100% output power
THD	<5% at 50 – 100% full load
Charging Efficiency	≥94% at nominal output power

⌄ ELECTRICAL OUTPUT

Output Voltage Range	150–1000 V DC
Maximum Current	CCS2: 200 A / GBT: 200 A / CHAdeMO: 150 A
Maximum Power	60kW
Maximum Power Per Connector	60kW
Connector Type	CCS2; GBT; CHAdeMO
Number of Connectors / Outputs	2
Cable Length	5 m, others optional

⌄ CONNECTIVITY AND COMMUNICATION

Network Connectivity	Ethernet (RJ45), Wi-Fi, 4G
Backend Protocol	OCPP 1.6J / 2.0 / 2.0.1

⌄ USER INTERFACE AND ACCESS CONTROL

Display / HMI	10" LCD Touch Screen
LED Status Indication	LED status indication
RFID	RFID: ISO / IEC 14443 A/B; MIFARE, 13.56 MHz
Authentication And Payment	App, QR Code, MAC Authentication (optional), Card Payment (optional)
Metering	2 x DC energy meter, CE-marked

⌄ ENVIRONMENTAL CONDITIONS

Operating Temperature	–25°C to 55°C
Storage Temperature	–30°C to 70°C
Altitude	≤2000 m
Humidity	5% to 95% non-condensing
Ingress And Impact Protection	IP54, IK10 (screen excluded)
Noise	<70 dB

⌄ SAFETY AND PROTECTION

Integrated Protections	Emergency stop button / MCCB 3P+N, 125 A / RDC-DD, 6 mA DC leakage detection / Overvoltage and undervoltage protection / Overcurrent protection / Output PE continuous continuity checking / Surge protection device (SPD), Type 2, fused / 2 x Insulation monitoring / Temperature monitoring
Physical Security And Access	Key-lock access door
Special Environmental Protection	Galvanised steel, powder-coated, salt-spray resistant

Cont'd on page 2

DC RAPID CHARGER – S3

⌂ 60kW

PRODUCT CODE

TP-EVPD060KW

☰ MECHANICAL DATA

Dimensions	913 x 622 x 1865 mm
Weight	277 kg
Mounting	Floor mounted
Cable Management	Cable support
Cooling System	Forced-air cooling

☰ COMPLIANCE AND STANDARDS

Charging Protocol Support	ISO 15118; DIN 70121; GB/T 27930; CHAdeMO 0.9 / 1.0
Regulatory Compliance	IEC 61851-1; IEC 61851-23; IEC 61851-21-2
Certification	CE Marked (LVD, EMC, RoHS)

End of Table