



AC 55" SCREEN, DUAL

2X22KW

 FLOOR MOUNTED

 PRODUCT DATASHEET / MAY 2026

 **Reliable**

Product Reliability

99%

 **Cloud Enabled**

Monitoring & Assistance

24/7

 **Built To Last**

Service Life

10Yr

KEY FEATURES

- ↳ Dual connectors enable simultaneous charging of two vehicles
- ↳ Supports dynamic load balancing and static load management
- ↳ Seamless integration with OCPP 1.6J / 2.0 / 2.0.1 protocol
- ↳ Integrated PME fault detection
- ↳ Three-phase connection
- ↳ 3-year warranty with an optional 2-year extension
- ↳ 55" Full HD display with customisable digital signage and multimedia
- ↳ Fully compliant with Smart Charge Points regulations for electric vehicles



DUAL AC, 55" SCREEN

2 x 22kW

PRODUCT CODE

TP-EVVA-AD32ATD / TP-EVVA-380-2B

⋮ ELECTRICAL INPUT	
Supply System	3P+N+PE, TN/TT
Supply Voltage	400 V AC ±10%
Supply Frequency	50/60 ±1 Hz
Rated Input Current	64 A
⋮ ELECTRICAL OUTPUT	
Output Voltage Range	400 V AC±10%
Maximum Current	64 A
Maximum Power	44 kW (2 x 22 kW simultaneous)
Maximum Power per Connector	22 kW
Connector Type	2 x Type 2
Shutter Type	2 x Type 2
Number of Connectors / Outputs	2
Cable Length	5 m, others optional
⋮ CONNECTIVITY AND COMMUNICATION	
Network Connectivity	Ethernet (RJ45) / Wi-Fi / 4G / BLE V5.0
Backend Protocol	OCPP 1.6J / 2.0 / 2.0.1
Local Load Management	Local Load balance (Optional)
⋮ USER INTERFACE AND ACCESS CONTROL	
Display / HMI	5" LCD Touch Screen and 55" LCD colour Screen
RFID	RFID: ISO/IEC 14443 A/B; MIFARE, 13.56 MHz
Authentication And Payment	App, QR Code, MAC Authentication, Card Payment (optional)
Metering	2 x MID meter, Class 1, CE-marked
⋮ ENVIRONMENTAL CONDITIONS	
Operating Temperature	-25°C to 50°C
Storage Temperature	-30°C to 70°C
Altitude	≤2000 m
Humidity	5% to 95% non-condensing
Ingress And Impact Protection	IP54, IK10 (screen excluded)
⋮ SAFETY AND PROTECTION	
Integrated Protections	Emergency stop button / 2 x RCBO, 3P+N, curve C, 40 A, 30 mA, type A / 2 x RDC-DD, 6 mA DC leakage detection / 2 x Overvoltage and undervoltage protection / 2 x Overcurrent protection / 2 x Output PE continuous continuity checking / 2 x Surge protection, 4kV / 2 x Contactor welding monitoring / Upstream protective conductor monitoring (Optional) / Temperature monitoring 2 pcs Optional
Physical Security And Access	Key-lock access door
Special Environmental Protection	Galvanised steel, powder-coated, salt-spray resistant

Cont'd on page 2

DUAL AC, 55" SCREEN

⌘ 2 x 22kW

PRODUCT CODE

TP-EVVA-AD32ATD / TP-EVVA-380-2B

⌘ MECHANICAL DATA

Dimensions	1108 x 428 x 1960 mm
Weight	200 kg
Mounting	Floor mounted
Cable Management	Cable support

⌘ COMPLIANCE AND STANDARDS

Regulatory Compliance	IEC/EN 61851-1:2017; IEC 61851-21-2:2018; IEC 62196-1:2014; IEC 62196-2:2016; IEC 62955-2018; IEC 61439-7-2018
Certification	CE Marked (LVD, EMC, RoHS)

End of Table