

Regular DC Charger 30kW, Wall-Mounted/Pedestal

 Datasheet

2025



Reliable

Product
Reliability

99%

Cloud Enabled

Monitoring &
Assistance

24/7









Built To Last

Service
Life

10Y

Key Features

- Single tethered connector, available as wall-mounted or stand-mounted
- Supports dynamic load balancing and static load management
- Seamless integration with OCPP 1.6J / 2.0 / 2.0.1 protocol
- Supports multiple payment options — app, RFID, credit card, and smartphone payments
- Three-phase connection
- 3-year warranty with an optional 2-year extension

 AC INPUT	AC Input	380/400VAC (±15%) 50/60Hz
	FLA Breaker Rating	50A / 63A
	Efficiency	≥ 94% at nominal output power
 DC OUTPUT	Output Voltage Range	150-1000VDC
	Max Output Current	CCS2 : 80A GBT : 80A CHAdEMO : 80A
	Connectors Quantity	1
 ENVIRONMENT	Operating Temperature	-4°F to 131°F (-20°C to 55°C)
	Protective Class	IP54, IK 10 (not including screen)
 COMMUNICATION	Communication	Ethernet, Wi-Fi, 4G
	Interface Protocol	OCP 1.6J / 2.0 / 2.0.1
 USER INTERFACE	Display	7" LCD Touch Screen
	Access Control	RFID : ISO/IEC 14443A/B Credit Card Reader - Optional
 MECHANICAL	Dimension Wall Mount (W X D X H)	29.53" x 13.07" x 20.47" (750mm x 332mm x 520mm)
	Dimension Pedestal (W X D X H)	29.53" x 11.42" x 64.96" (750mm x 290mm x 1650mm)
	Weight	176 lbs (80kg)
	Connector Cable Length	CCS2 - 16 ft (5 m) CHAdEMO - 16 ft (5 m) GBT - 16 ft (5 m)
 PROTECTION	Input Protection	Surge Protection Over Voltage, Under Voltage (Optional) Over Current, Missing Ground (Optional)
	Output Protection	Short circuit protection Insulation protection Over temperature protection
 REGULATION	Charging Protocol	ISO-15118, DIN 70121, GB/T 27930, CHAdEMO 0.9, 1.0
	Regulatory Compliance	IEC 61851-1, IEC 61851-23, IEC 61851-21-2
	Certificate	CE