

V2G DC CHARGER

7KW

WALL MOUNTED OR STAND PEDESTAL

PRODUCT DATASHEET / MAY 2026



 **Reliable**

Product
Reliability

99%

 **Cloud Enabled**

Monitoring
& Assistance

24/7

 **Built To Last**

Service
Life

10Yr

KEY FEATURES

- Single tethered connector
- Remote software updates and diagnostics
- Seamless integration with OCPP 1.6J/2.0/2.0.1 protocol
- Supports multiple payment options — app, RFID, credit card, and smartphone payments
- Single-phase connection
- Rapid charging
- Supports multiple output options: CCS1, CCS2 and CHAdeMO
- 7" LCD Touch Screen
- 3-year warranty with an optional 2-year extension



V2G DC CHARGER

⌂ 7kW

PRODUCT CODE

TP-EVPD-007KS-V2G

⌄ ELECTRICAL INPUT	
Supply System	1P+N+PE, TN/TT
Supply Voltage	230 V AC (±10%)
Supply Frequency	50/60 ±1 Hz
Rated Input Current	32 A
Power Factor	≥0.98 at 50 – 100% output power
THD	<5% at 50 – 100% full load
Charging Efficiency	≥94% at nominal output power
⌄ ELECTRICAL OUTPUT	
Output Voltage Range	230 V AC (±10%)
Maximum Current	36 A
Maximum Power	7 kW
Connector Type	Type 2
Number of Connectors / Outputs	1
Cable Length	5 m, others optional
⌄ BIDIRECTIONAL OPERATION	
Discharge Input Voltage Range	300–1000 V DC
AC Output Voltage	230 V AC (±10%)
AC Output Current	31.8 A
Rated Discharge Efficiency	≥94% at nominal output power
⌄ CONNECTIVITY AND COMMUNICATION	
Network Connectivity	Ethernet (RJ45) / Wi-Fi / 4G
Backend Protocol	OCPP 1.6J / 2.0 / 2.0.1
⌄ USER INTERFACE AND ACCESS CONTROL	
Display / HMI	5" LCD Touch Screen
LED Status Indication	LED status indication
RFID	RFID: ISO/IEC 14443 A/B; MIFARE, 13.56 MHz
Authentication And Payment	App, QR Code, MAC Authentication, Card payment (optional)
Metering	MID meter, Class 1, CE-marked
⌄ ENVIRONMENTAL CONDITIONS	
Operating Temperature	–25°C to 55°C
Storage Temperature	–30°C to 70°C
Altitude	≤2000 m
Humidity	5% to 95% non-condensing
Ingress And Impact Protection	IP54, IK10 (screen excluded)
Noise	<70 dB

Cont'd on page 2

V2G DC CHARGER

⌂ 7kW

PRODUCT CODE

TP-EVPD-007KS-V2G

⌄ SAFETY AND PROTECTION	
Integrated Protections	Emergency stop button / RCBO, 1P+N, curve C, 63 A, 30 mA, type A / RDC-DD, 6 mA DC leakage detection / Overvoltage and undervoltage protection / Overcurrent protection / Output PE continuous continuity checking / Surge protection, 4kV / Contactor welding monitoring / Upstream protective conductor monitoring (Optional) / Temperature monitoring 2 pcs (Optional) / Anti-islanding protection – to be confirmed
Physical Security And Access	Key-lock access door
Special Environmental Protection	Galvanised steel, powder-coated, salt-spray resistant
⌄ MECHANICAL DATA	
Dimensions	750 x 332 x 520 mm
Weight	80 kg
Mounting	Wall Mounted / Stand pedestal
Cable Management	Cable support
Cooling System	Forced-air cooling
⌄ COMPLIANCE AND STANDARDS	
Charging Protocol Support	ISO 15118; DIN 70121
Discharging Protocol Support	ISO 15118-20
Regulatory Compliance	IEC 61851-1; IEC 61851-23
Certification	CE Marked (LVD, EMC, RoHS)

End of Table