

Product Datasheet

⌘ DC AdVision Rapid Charger · Floor-Mounted

120kW



✓ Reliable

Product
Reliability

99%

✓ Cloud Enabled

Monitoring
& Assistance

24/7

✓ Built To Last

Service
Life

10Y

Key Features

- ✓ Dual tethered connectors allow for simultaneous charging of two vehicles
- ✓ Remote software updates and diagnostics
- ✓ Seamless integration with OCPP 1.6j protocol
- ✓ Supports multiple payment options — app, RFID, credit card, and smartphone payments
- ✓ 10"LCD Touch Screen and 32"LCD Colour Screen
- ✓ 3-year warranty with an optional 2-year extension
- ✓ Supports multiple output options: CCS2 and CHAdeMO
- ✓ Approved for OZEV grant eligibility

⌘ AC INPUT	AC Input	400VAC (±15%) II 50Hz
	FLA II Breaker Rating	200A / 250A
	Efficiency	≥ 94% at nominal output power
⌘ DC OUTPUT	Max Output Voltage	150-1000VDC
	Max Output Current	CCS2 : 350A GBT : 250A CHAdEMO : 200A
	Connectors	CCS2 and GBT and CHAdEMO
	Connectors Quantity	2
	Operating Temperature	-4°F to 122°F (-20°C to 50°C)
⌘ ENVIRONMENT	Protective Class	IP54
	Communication	Ethernet, Wi-Fi, 4G
⌘ COMMUNICATION	Interface Protocol	OCPP 1.6J
	Display	10" LCD Touch Screen and 32" LCD Colour Screen
⌘ USER INTERFACE	Access Control	RFID : ISO/IEC 14443A/B Credit Card Reader - Optional
	Dimension Wall Mount (W X D X H)	39.96" x 29.73" x 81.11" (1015mm x 755mm x 2060mm)
⌘ MECHANICAL	Weight	903lbs (400kg)
	Connector Cable Length	CCS2 - 16 ft (5 m) CHAdEMO - 16 ft (5 m) GBT - 16 ft (5 m)
	Input Protection	Surge Protection Over Voltage, Under Voltage (Optional) Over Current, Missing Ground (Optional)
⌘ PROTECTION	Output Protection	Short circuit protection Insulation protection Over temperature protection
	Charging Protocol	ISO-15118 , DIN 70121, GB/T 27930 , CHAdEMO 0.9, 1.0
⌘ REGULATION	Regulatory Compliance	IEC 61851-1, IEC 61851-23, IEC 61851-21-2
	Certificate	CE