

## **Product Datasheet**

Dual 22kW











Monitoring & Assistance 24/7

Built To Last

Service Life 10Y

## Key Features

- Dual connectors allow for simultaneous charging of two vehicles
- Supports dynamic load balancing and static load management
- Seamless integration with OCPP 1.6j protocol
- Three-phase connection (11/22kW), with the option to downgrade to 7kW
- Integrated PME fault detection
- 3-year warranty with an optional 2-year extension
- Fully compliant with Smart Charge Points regulations for electric vehicles
- Approved for OZEV grant eligibility

| L1L2L3N + PE, Three-Pha  | Power                            |                 |
|--|----------------------------------|-----------------|
| 305-457V AC, L1L2L3N + PE, Three-Pha                                     | Input/Output AC Voltage          | AC INPUT        |
| 32A AC   | Rated Current                    |                 |
| 50/60±1  | Rated AC Frequency               |                 |
| 22kW Three-Pha   | Rated Output Power               |                 |
| Тург   | EV Gun Type                      |                 |
|  | EV Gun (PCS)                     |                 |
| 5m Others (option  | EV Charger Cable                 |                 |
| -20°C to 55  | Operating Temperature            |                 |
| IP   | Degree of Protection (IP Class)  | ENVIRONMENT     |
| LAN (optior  | Network Connectivity             |                 |
| Wi-Fi (option  |                                  | COMMUNICATION   |
| 4G (option   |                                  |                 |
| BLE V5.0 (option   |                                  |                 |
| OCPP V1.6/WSS (Yes if has network connectiv                              |                                  |                 |
| Local Load Balance (option   |                                  |                 |
| Active Multi-Standard, Mifare 13.56M                                     | RFID Reader                      | LIGER INTERFACE |
| 5" LCD Touch Scre  | НМІ                              | USER INTERFACE  |
| MID, CE, Accuracy Class: ±1.0 (option                                    | Power Meter                      |                 |
| RCD Type B (with external RCBO Type                                      | Protection                       |                 |
| Overvoltage and undervoltage protecti                                    |                                  | SAFETY          |
| Overcurrent protecti   |                                  |                 |
| Overtemperature protecti   |                                  |                 |
| Upstream protective conductor monitori                                   |                                  |                 |
| Output PE continuous continuity checki                                   |                                  |                 |
| Surge protection: 4  |                                  |                 |
| Output short circuit protecti  |                                  |                 |
| Contactor welding monitori   |                                  |                 |
| Temperature monitoring 2pcs (option                                      |                                  |                 |
| 17.34" x 6.67" x 54.88" (440.5mm x 169.5mm x 1394m                       | Dimension Wall Mount (W X D X H) | MECHANICAL      |
| 143.30lbs (65  | Weight                           | MEGINATIONE     |
| Stand Pedes  | Mounting                         |                 |
|  | Standard                         |                 |
| IEC/EN 61851-1:2017;IEC 61851-21-2:20                                    | Otandard                         |                 |
| IEC/EN 61851-1:2017;IEC 61851-21-2:20<br>IEC 62196-1:2014;IEC 62196-2:20 | Standard                         | REGULATION      |

CE

Certificate